

Codering:	20220349GK																								
Betreft	Gecontroleerde kwaliteitsverklaring																								
Toepassing:	NTA 8800 Basisopname																								
Fabrikant:	Faber Betonpompen BV																								
Type:	Isolite 75 (schuimbeton)																								
Ingangsdatum verklaring	26-10-2022																								
Geldigheidsduur verklaring																									
<table border="1"> <thead> <tr> <th>Begane grond vloer</th> <th>R_c [m²K/W]</th> </tr> </thead> <tbody> <tr> <td>Dikte Isolite 75 [mm]</td> <td></td> </tr> <tr> <td>100</td> <td>1,08</td> </tr> <tr> <td>200</td> <td>2,15</td> </tr> <tr> <td>300</td> <td>3,23</td> </tr> <tr> <td>330</td> <td>3,55</td> </tr> <tr> <td>400</td> <td>4,30</td> </tr> <tr> <td>420</td> <td>4,52</td> </tr> <tr> <td>500</td> <td>5,38</td> </tr> <tr> <td>600</td> <td>6,45</td> </tr> <tr> <td>700</td> <td>7,53</td> </tr> <tr> <td>800</td> <td>8,60</td> </tr> </tbody> </table>		Begane grond vloer	R_c [m²K/W]	Dikte Isolite 75 [mm]		100	1,08	200	2,15	300	3,23	330	3,55	400	4,30	420	4,52	500	5,38	600	6,45	700	7,53	800	8,60
Begane grond vloer	R_c [m²K/W]																								
Dikte Isolite 75 [mm]																									
100	1,08																								
200	2,15																								
300	3,23																								
330	3,55																								
400	4,30																								
420	4,52																								
500	5,38																								
600	6,45																								
700	7,53																								
800	8,60																								

De R_c-waarde mag alleen gebruikt worden als aangetoond wordt dat:

- er een dampremmende laag tussen de bodem en Isolite 75 aanwezig is.
- de betreffende begane grondvloer bestaat uit Isolite 75